

Boost2o is a range of variable or fixed speed booster sets comprising 2, 3, 4 or 5 WRAS approved pumps.

MULTI PUMP BOOSTER SETS

On site builds available.

With or without break tanks.

Controlled via drives with LCD displays which can indicate system overviews and operating parameters, such as pressure, speed, power absorbed and many other factors.

Fully connectable to any BMS system, units are available with numerous networking configurations.

Pumps are mounted on a steel base frame which can be complete with fully WRAS approved break tank.



Standard items include;

- Single or multi pump units
- Stainless steel manifolds
- Fixed speed or variable speed
- WRAS approved pump

Optional items include;

- Frame mounted pre packaged units c/w tank
- On site build
- Modem connectivity

Boost2o sets are energy conscious.

ENERGY EFFICIENT OPERATION

As soon as the system pressure drops due to a water demand, one pump will run in order to meet the flow rate demanded. Starting of the second pump occurs in a cascade sequence once the first pump has reached its maximum rotation speed. Required pressure can be adjusted by means of the Active Driver + and - keys. External output signals and input signals for full communication with building management systems.

Boost2o sets are automatically protected against;

- Pump current surge
- Dry running conditions
- Low power supply voltage
- Overheating of components

 Would you prefer 2 talk? Please contact us.